



Connectable with various ECR system



easy to controll



adjustable view angle of indicator

# PDI INDICATOR

## Check-out scale Indicator

- Suitable to use in narrow place as simple indicator
- Connectable with various ECR & POS system
- Offering suitable solution to various shop such as supermarket and general store etc



CAS

# PDI | Check-out scale Indicator

## Adjustable view angle of indicator



The user can view weight in various angle with adjustment of view angle of indicator

## SPECIFICATIONS

Model	PDI	
Applied voltage for load cell	DC 5V(350Ω maximum 8 possible connections)	
Zeroing range	0~2 mV/V	
Input sensitivity	0.5 uV/D (OIML, )Ntep, KS	
	0.5 uV/D (Non OIML, )Ntep, KS	
A/D internal resolution	1/520,000	
A/D external resolution	1/10,000 (NTEP, )OIML, KS	
	1/20,000 (Non NTEP, )OIML, KS (Possible with the use of sufficient output at 2mV/V L/C)	
A/D conversion speed	80 rounds/second	
Sign for status	STABLE, NET, ZERO, COM	
Weight display	LCD(6 digit + Sign)	
AC Adapter	AC 100~240 V(DC 12V, 1.25A)	
Operating temperature	-10°C ~ 40°C	
Product size(mm)	141(W) X 101(D) X 382(H)	
Product weight	500g	
Product weight	Standard	COM1(RS-232 Printer & PC Interface )
	Option	USB

## FEATURES

- Suitable for the Checkout scale and weighing system
- Easy operations
- Simple and prompt full digital calibration (automatic weight setup at once)
- Weight backup functions  
[restoring weight at the power supply On/Off]
- Multiple weights setup functions  
[5 point input weight setup]
- Command Mode [ ECR Protocol]
- 6 line [basic]/4 line load cell Input

# CAS

CAS BLDG., # 440-1, SUNGNAE DONG,  
GANGDONG GU, SEOUL, KOREA

TEL\_ 82 2 2225 3500

FAX\_ 82 2 475 4668

<http://www.globalcas.com>

Specifications are subject to change for improvement without prior notice.

## Connectable with various platform

Connectable with various ECR system, POS system and check out scale



## OPTIONS

- USB Interface

## DIMENSIONS

