





Technical Specifications...

	WM-Nano 'L' Type
Packs Per Minute:	15ppm
Wrapping Capacity:	20g-3500g
Weighing Capacity:	40g-15000g
Wrapping Size:	Depth: 127~254mm (5"~10"); FP: 80mm (3.15") Width: 150~350mm (5.9"~13.8"); FP: 120mm (4.72") Height: 10~130mm (0.4"~5.1") Tray height: ≤45mm (1.8") Note: It is not possible to achieve all three maximum dimensions contemporary on the machine. FP means Foot Print size of the tray (bottom size).
Tray:	PSP, PP
Film Type:	Poly or PVC
Film Size:	400 · 450 · 500 · 550 · 560mm (15.75" · 17.72" · 19.69" · 21.65" · 22.05") Max. φ: 200mm (7.9")
Power:	Voltage: 220~240V Frequency: 50/60Hz
Operating Temperature:	5°C~35°C (41°F~95°F)
Humidity:	20%~85% R.H.
Weight:	Wrapper: 90kg; Wrapper & scale: 100kg
Noise:	73db

 **ISHIDA**

Specifications and design are subject to change without notice.



ISHIDA CO., LTD.

44 SANNO-CHO, SHOGOIN, SAKYO-KU
KYOTO, 606-8392 JAPAN
PHONE: 81-75-771-4141
FACSIMILE: 81-75-751-1634
URL: <http://www.ishida.com>

