

# CI-600A SERIES | Weighing Controller

## Graphic User Interface (GUI)



<Simple Type O-601A>

<Controller Type O-605A>

## FEATURES

- High A/D conversion speed (200 times/sec)
- High display resolution 1/10,000
- User-friendly interface (4.3" Full Graphic TFT LCD)
- Shielded against electrical noise (RR & EM)
- Storing 100 items' information
- USB data backup
- Self-hardware test function
- Weight Back-up
- PC software to manage indicator
- Various communication interfaces

## OPTION

- Analog Out Card (V-out (0-10V)/I-out (4-20mA))
- RS485/RS422
- BCD Out Card
- Printer
- Remote display



CAS BLDG. # 440-1, SUNGNAE-DONG,  
GANGDONG-GU, SEOUL, KOREA  
TEL. 82 2 2225 3500  
FAX. 82 2 475 4666



<http://www.globalcas.com>

Specifications are subject to change for improvement without prior notice.

## SPECIFICATIONS

Model	CI-601A	CI-605A
Load cell excitation voltage	DC 5V	
Load cell connection	10 EA (350Ω)	
Load cell input range	-2.0mV/V ~ 3.0mV/V	
Input Sensitivity	0.5 μV/D (Approval), 0.3 μV/D (Non-Approval)	
A/D Internal resolution	1/520,000	
A/D Display resolution	1/10,000 (OIML / NTEP / KS), 1/20,000 (Non approval)	
A/D Conversion speed	200 times/sec	
A/D conversion method	Sigma-delta	
Display	4.3" TFT Color LCD	
Key	Numeric Key 10, Function Key 9	
Interface	Standard	RS232 (COM1, COM2)
	Option	RS422, RS485, Analog_out / BCD_out
External I/O	Input 4 / Output 6	
Power	AC	AC 100 ~ 240V 50/60Hz
Operating Temp	-10 °C ~ 40 °C	
Approval	OIML, CE	
Dimensions (W x D x H) mm	192.9 x 190.2 x 98.4	
Weight (kg)	1.5	

## DIMENSIONS



0-61103102

## INDUSTRIAL WEIGHING SOLUTION™



# CI-600A SERIES

## Weighing Controller

CI-600A series offers fast and accurate weighing and easy operating system via High-performance A/D converter and user-friendly graphic interface. Suitable for a wide variety of applications from general platform scales to advanced weighing equipment such as Truck Scales, Hopper Scales, Packer Scales and Checker Scales




# CI-600A SERIES



## Features

### High weighing performance

High speed A/D conversion with excellent processing capabilities (200 times/sec.) for fast response.  
High display resolution of 1/10,000 for all input range.



### Shielded against noise (RFI & EMI)

CI-600A series is shielded against noises such as RFI and EMI, offering supreme stability in rough environmental conditions.



### Display protection cover

Protecting the display against foreign substances and external shocks.



### Easy setup

Easy setup with parameter setup messages.



### Various key function

CI-600A series offers numeric keys and 9 functions. Also, Users can setup 3 short-cut keys (F1, F2 and F3) with preferred or commonly used functions for greater ease of use.

### User-friendly interface

Various setup messages and value, function icons and weighing information are easily viewed on 4.3" Full Graphic TFT LCD.

### USB data backup

Backing up Weighing data through USB port.



## Weighing Controller

## Communication Interface



### Various communication interfaces

2 RS232C ports are built in as a standard, also 3 communication cards can be used simultaneously.

### Standardized communication card

Standardized communication card of Slot type can be easily changed and installed.



### Terminal block

Easy to wire and connect with external Equipment such as remote display, printer and PLC via terminal block.



## Application / Software

### Various Application

Suitable for a wide variety of applications from general platform scales to advanced weighing equipment such as Truck Scales, Hopper Scales, Packer Scales and Checker Scales.



### Compatibility with various printers

Compatible with Ticket printers and label printers.

### PC Software

CI-600A PC software allows users to manage setup value and backup weighing data to PC.

